



รับประกันคุณภาพ
อะไหล่แท้และบริการ

องค์กรแห่งแรกของไทย



ที่ได้มาตรฐานคุณภาพสินค้าและบริการด้านวิศวกรรม
ISO 9001 : 2015



GET IT NOW!!
SUPER HOT
จ๊ว แต๊ จ๊ว

ขนาดเล็ก | ยากว้นโบอนุญาตพกพา



SPECIFICATIONS

- 160 CHANNELS, 40 FREE MEMORIES
- 214 CODES OF DCS
- 51 GROUPS OF CTCSS
- BABY MONITOR (BBM)
- ROGER BEEP SOUND (ROGER)
- BATTERY SAVER
- PTT ID (TYPE OF PTT ID)
- BUSY CHANNEL LOCK OUT
- TIME-OUT TIMER (TOT)



BABY MONITOR



BATTERY SAVER



BATTERY 1100 mAh.



214 CODES OF DCS



TIME - OUT TIMER

SPECIFICATION ID2462

GENERAL

FREQUENCY COVER RANGE	245.0000 - 246.9875 MHz.
CHANNEL	160 Channels, 39 Free Memories
CHANNEL SPACING	12.5 KHz.
OPERATION TEMPERATURE RANCE	-20 °C ~ +50 °C
FREQUENCY STABILITY	± 5 ppm (-20 °C ~ +50 °C)
POWER SUPPLY REQUIERMENT	3.7V DC.
CURRENT STAND-BY	20mA.
DIMENSIONS	96 x 58 x 32 (H x Wx D)
WEIGHT	95g. (with battery)
COLOR	Red



BATTERY 1100 mAh.



USB



ADAPTOR



ANTENNA

TRANSMITTER

OUTPUT POWER	Hi : 0.5w./ Lo : 0.1w.
SUPRIOUS RADIATION	63dB.
ADJACENT CHANNEL POWER	< -63dBm.
MAX. FREQUENCY DEVIATION	± 2.5 KHz.
TX DISTORTION	< 5%



SMALL TALK



BELF CLIP

RECEIVER

SENSITIVITY	< 0.25µV. at 12dB./ SINAD
SQUELCH SENSITIVITY	< 0.158µV.
SELECTIVITY	- 65dBm.
INTERMODULATION	65dB.
AUDIO OUTPUT MAX	> 500 mW.
AUDIO DISTORTION	< 5% at 8 Ohm Speaker



HAND STRAP



USER'S MANUAL